



ETAG 005

04

0836

DECLARATION OF PERFORMANCE

Decothane[®] Roof Waterproofing Systems

02	09	15	20	600	0	000012	1148
02	09	15	20	600	0	000010	1148

1. Product Type: Unique identification code of the product-type:	Decothane[®] Roof Waterproofing Systems
2. Type batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):	Decothane[®] Roof Waterproofing Systems (Batch No. see packaging)
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:	Decothane[®] Roof Waterproofing Systems is for use as a liquid-applied roof waterproofing kit to resist the passage of water to the building's internal structure, where Essential Requirements 2 Safety in case of fire, 3 Hygiene, health and the environment and 4 Safety in use of Directive 89/106/EEC, including the aspect of durability.
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):	Decothane[®] Roof Waterproofing Systems Sika Limited Sika Liquid Plastics Sika House Miller Street Preston PR1 1EA United Kingdom
5. Contact Address: Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):	Not Relevant (see 4)
6. AVCP: System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:	System 3
7. Notified body (hEN): In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard:	Not Relevant (see 8)

Declaration of Performance



8. Notified body (ETA):

In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued:

Approval body British Board of Agrément (no.0836) issued an ETA-03/0052 on the basis of ETAG 005-6:2000.

9. Declared performance

Essential characteristics	Performance			Test Standard	Harmonised technical specification
	Omega 15	Gamma 20	Delta 25		
External fire performance Part 1 – 4	B _{Roof} (t1) B _{Roof} (t2) B _{Roof} (t3) B _{Roof} (t4)	B _{Roof} (t1) ⁽¹⁾ B _{Roof} (t2) ⁽¹⁾ B _{Roof} (t3) ⁽¹⁾	B _{Roof} (t1) ⁽¹⁾	ENV 1187 EN 13501-5	ETAG 005-6:2000
Reaction to fire	NPD (Euroclass S F)	Euroclass E	Euroclass E	EN 13501-1	
Categorization by working life:	W3	W3	W3	According to ETAG 005-6:2000, 4.3.3	
Categorization by climatic zones:	M and S	M and S	M and S		
Categorization by imposed loads: most compressible substrate: least compressible substrate:	P4 P4	P4 P4	P4 P4		
Categorization by roof slope:	S1 to S4	S1 to S4	S1 to S4		
Categorization by surface Temperature: Lowest: Highest:	TL3 TH4	TL3 TH4	TL3 TH4		
Statement on dangerous substances:	None contained	None contained	None contained		
Slipperiness [slope (°)/friction coefficient]: no grit (dry) grit at 0.25 kg·m ⁻² (dry) grit at 1.00 kg·m ⁻² (dry) no grit (wet) grit at 0.25 kg·m ⁻² (wet) grit at 1.00 kg·m ⁻² (wet)	18.7/0.34 29.0/0.55 32.0/0.62 16.7/0.30 28.3/0.54 32.0/0.62	18.7/0.34 29.0/0.55 32.0/0.62 16.7/0.30 28.3/0.54 32.0/0.62	18.7/0.34 29.0/0.55 32.0/0.62 16.7/0.30 28.3/0.54 32.0/0.62	EN 13893	

⁽¹⁾ Classification under BS 476-3: 1958 is assessed as EXT.F.AA. Results of tests are given in the Evaluation Report



10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



R&D Manager



Technical Manager

04, 2013

Ecology, Health and Safety Information (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet (MSDS) containing physical, ecological, toxicological and other safety related data.

Further Information

Contact: Sika Liquid Plastics
 Tel: 01772 259781
 Fax: 01772 255670
 Email: liquidplastics@uk.sika.com
www.liquidplastics.co.uk

Legal note:

This information is given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



Sika Limited (Registered Office)
 Watchmead
 Welwyn Garden City
 Hertfordshire
 AL7 1BQ
 United Kingdom
 Phone +44 1707 394444
 Telefax +44 1707 329129



Certificate No. EMS 588023



Certificate No. FM 588020