



EN 13970:A1:2007

16

1508/1213

## DECLARATION OF PERFORMANCE

### S-Vap 7000 E DP

02	09	45	11	400	0	000012	1195
----	----	----	----	-----	---	--------	------

<b>1. Product Type:</b> Unique identification code of the product-type:	<b>S-Vap 7000 E DP</b>
<b>2. Type</b> batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):	<b>S-Vap 7000 E DP ( Batch No See packaging)</b>
<b>3. Intended use</b> or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:	<b>Flexible sheets for waterproofing. Bitumen vapour control layers.</b>
<b>4. Name, registered trade name</b> or registered trade mark and contact address of the manufacturer as required under Article 11(5):	<b>S-Vap 7000 E DP</b>  <b>Sika Limited</b> <b>Sika Liquid Plastics</b> <b>Sika House</b> <b>Miller Street</b> <b>Preston</b> <b>PR1 1EA</b> <b>United Kingdom</b>
<b>5. Contact Address:</b> Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):	<b>Not Relevant (see 4)</b>
<b>6. AVCP:</b> System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:	<b>AVCP 3</b>
<b>7. Notified body (hEN):</b> In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard:	<b>EN13970:A1:2007</b> <b>Notified testing laboratory 1508, testing regarding fire behavior and issues – testing report no.KB-Hoch-120601</b>  <b>Notified testing laboratory 1213, testing regarding water vapour permeability and water tightness and issued – testing report no. 91221/10-I and 99572/12</b>

Declaration of Performance



**8. Notified body (ETA):**  
 In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued:

**Not relevant (see 7)**

**9. Declared performance**

Essential characteristics	Performance	Test Standard	Harmonised technical specification
Reaction to fire	Euroclass E	EN 13501-1	EN 13970:A1:2007
Water Vapour Permeability	>1500m	EN 1931	
Watertightness	Pass	EN 1928	
Resistance to impact	≥ 300mm	EN 12691	
Tensile Strength Longitudinal: Transversal	≥800N/50mm ≥800N/50mm	EN 12311-1	
Elongation at Break	≥2.5%	EN 12311-1	
Shear resistance of joints	≥400N/50mm	EN 12317-2	
Cold Bending Test	<-30°C	EN 1109	
Tear Resistance	>100N	EN 12310-1	
Durability against alkaline	Pass	Annex C	
Durability against ageing	Pass	EN 1296/EN1931	



Roofing  
 Declaration of Performance  
 Edition 04.2016  
 Identification no. 02 09 45 11 400 0 000012 1195  
 Version no. 01

## 10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Head of R&D - Sika Ltd



Product Manager – LAM

04, 2016

## Ecology, Health and Safety Information (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet (MSDS) containing physical, ecological, toxicological and other safety related data.

## Further Information

**Contact: Sika Liquid Plastics**  
**Tel: 01772 259781**  
**Fax: 01772 255670**  
**Email: [liquidplastics@uk.sika.com](mailto:liquidplastics@uk.sika.com)**  
**[www.liquidplastics.co.uk](http://www.liquidplastics.co.uk)**

### Legal note:

This information is given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Limited (Registered Office)  
 Watchmead  
 Welwyn Garden City  
 Hertfordshire  
 AL7 1BQ  
 United Kingdom  
 Phone +44 1707 394444  
 Telefax +44 1707 329129



Certificate No. EMS 588023



Certificate No. FM 588020

