

Sika® Flexistrip

Preformed Strip Sealant

Product Description Sika® Flexistrip is a preformed strip sealant reel on a paper release liner for use with Sika Liquid Plastics Liquid Applied Roof Membranes.

Uses For treatment of boltheads and fixings prior to application of Sika Liquid Plastics Liquid Applied Roof Membranes.

Technical Data

Colour Off-White

Length 15 metre

Width 50mm

Storage

Storage Conditions Store in original packaging in a location away from sources of heat or ignition, dampness and extremes of temperature. Keep protected from rain and sunlight.

Preparation

Installation Methods / Tools Where necessary, materials should be cut with a knife or scissors. After cleaning and priming the fixing as required, pre-cut 50mm squares, remove the backing and fix by light pressure to the edges of the patches. Do not exert hard pressure in an attempt to form the tape to contours. On completion, keep clean and avoid foot pressure damage prior to coating with the Sika Liquid Plastics Liquid Applied Roof Membranes.

Value Base All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

Ecology, Health and Safety Information A Safety Data Sheet following EC-Regulation 1907/2006, Article 31 is not needed to bring the product to the market, to transport or to use it. The product does not damage the environment when used as specified.



REACH	European Community Regulation on chemicals and their safe use (REACH: EC 1907/2006) This product is an article within the meaning of Regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. Therefore, there are no registration requirements for substances in articles within the meaning of Article 7.1 of the Regulation. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) from the candidate list published by the European Chemicals Agency in concentrations above 0.1 % (w/w).
Protective Measures	Local safety regulations must be observed.
Transportation Class	The product is not classified as hazardous good for transport.
Disposal	Any Disposal must be according to local regulations.

Disclaimer

The information, and, in particular, the recommendations relating to the application and end-use of Sika Liquid Plastics products, are given in good faith based on Sika Liquid Plastics' current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika Liquid Plastics' recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika Liquid Plastics reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

General Information

Specification Assistance NBS is the industry standard specification system, which allows architects, specifiers and engineers to insert clauses into specifications by manufacturer and product, making the process quicker and more efficient. We are members of NBS Plus and therefore detailed up-to-date product information is readily available to create accurate specifications.

Contact Details

For further information please contact:
Sika Liquid Plastics
Iotech House
Miller Street
Preston
Lancashire
PR1 1EA

Enquiry line: +44 (0)1772 259781
Fax: +44 (0)1772 255670
e-mail: info@liquidplastics.co.uk

